



ASEMEPIIRDED



Valmistatud 50/55 tsingitud terastorudest, mis on kaitstud kolmekordse pinnatöötlustega – kuumtsingitud tsingikiht, kroomkate ja vastupidav pinnaviimistlus tagavad suurepärase korrosioonikindluse ka kõige niiskemates ja agressiivsemates keskkondades. Boksid pakuvad lehmadele mugavat ja turvalist puhkeala, piirates samas liigset liikumist ning aidates säilitada farmi sisekorra ja hügieeni. Bokside mõõtmeid saab kohandada vastavalt karja suurusele ja farmi eripäradele. Tugev raamkonstruktsioon koosneb painutatud torudest ja poltühendustest, mis vähendavad keevitustööde vajadust ja pikendavad kasutust. Biooniline disain järgib loomade loomulikku kehahoidu, tagades neile mugava puhkeasendi, samal ajal kui raamiku unikaalne kuju kaitseb loomi põrutuste ja vigastuste eest.



Spetsifikatsioon

Post	Ø 75mm, tsingitud
Ribirest	Ø 48mm, tsingitud
Toetuslatt	Ø 60mm, tsingitud
Kaelapiirde varras	Ø 42mm, tsingitud
Ühendusvardad	3mm ja 5mm terasplaat, Q235 kuumtsingitud
Laius	0.7m - 1.2m



CATTLE STALLS

Manufactured from 50/55 galvanized steel tubes and protected by a triple surface treatment—hot-dip galvanized zinc coating, chrome coating, and a durable surface finish—ensuring excellent corrosion resistance even in the most humid and aggressive environments. The stalls provide cows with a comfortable and safe resting area while limiting excessive movement and helping maintain order and hygiene within the farm.

The dimensions of the stalls can be customized according to herd size and farm-specific requirements. The robust frame construction consists of bent steel tubes and bolted connections, reducing the need for welding and extending service life. The bionic design follows the animals’ natural posture, ensuring a comfortable resting position, while the unique frame shape protects animals from impacts and injuries.

Specification

Post	Ø 75mm, galvanized
Rail	Ø 48mm, galvanized
Support bar	Ø 60mm, galvanized
Neck rail	Ø 42mm, galvanized
Connecting rods	3mm and 5mm steel plate, Q235 hot-dip galvanized
Width	0.7m - 1.2m